

# SAFETY LANYARD

## TX/L2

Art. 3744



CT 15  
High Tensile Steel  
Opening 18mm



CT 20  
High Tensile Steel  
Opening 17mm



CT 15  
High Tensile Steel  
Opening 18mm



CT 20  
High Tensile Steel  
Opening 17mm



CT 50  
High Tensile Steel  
Opening 50mm



CT 60  
Aluminum Alloy  
Opening 60mm



CT 110  
Aluminum Alloy  
Opening 110mm



Art. Nr	Connector to Shock Absorber	Connectors to Free Ends
3744/151515	CT15	2xCT15
3744/152020	CT15	2xCT20
3744/155050	CT15	2xCT50
3744/156060	CT15	2xCT60
3744/15110110	CT15	2xCT110
3744/201515	CT20	2xCT15
3744/202020	CT20	2xCT20
3744/205050	CT20	2xCT50
3744/206060	CT20	2xCT60
3744/20110110	CT20	2xCT110

### Safety Lanyard with Shock Absorber - TX/L2

- Conforms to EN 355
- 27 mm heavy duty webbing
- Teflon coated webbing for oil and water repellency
- Lengths from 1,10m to 2,00m (including end fittings)
- Various end fittings available to customer request
- Material - 100% Polyester